



Quick Check[®] On-Line Verifiers

Bar code verification is more than just scanning a bar code to see if it can be read. Verification is a process of decoding the data, measuring critical key characteristics, and assuring that the bar code will be readable in a wide variety of environments and scanning systems. By placing this verification “on-line”, you can reduce costly waste of time, resources, and labor right at the source of potential problems.

The Quick Check series of on-line bar code verifiers provides continuous inspection of labels as they are being printed, applied, stacked, or handled. Bar codes should be verified by decodability, readability, and overall quality as close to generation as possible. Our product design gives you the flexibility to place an on-line verifier into your process precisely where it will do the most to improve productivity, reduce cost, and increase quality.

The Model 10, used most often with direct thermal or thermal transfer printing, incorporates a laser verifier which is powered by the printer itself. The Model 20 uses a laser verifier separate from the main controller for “print-and-apply” or conveyor verification arrangements. The Model 20 has an internal power supply. Both verifiers read one-half inch high bar codes at speeds of up to eight inches per second.

The Model 10 can be programmed to use data about the quality of the bar codes in process to automatically control the printer’s pause function or to illuminate an indicator light, activate an external alarm, shut down the system, or initiate other functions of your choice. The Model 20 performs the same automated command functions as the Model 10, but because of its detachable verification design, the Model 20 can also be programmed to control conveyor and other machine functions.

Features & Benefits

Precise, Continuous Bar Code Verification

Automated Monitoring of Your Bar Code production

Real-Time Quality Control

Flexible, Easy-to-Learn/Use Programming

Poor quality bar codes can bring a lot more problems than just short-term process costs and productivity losses. Unreadable or incorrect bar codes can cause massive shipping returns, database corruption, and even customer fines. The accuracy, readability, and compliance of each and every bar code we use is critical. All the productivity and cost savings we expect when we institute bar code programs can only be realized if we ensure the quality of the bar codes themselves.

Quick Check® On-Line Verifiers

Performance

- Programmable For:** No Read, Warnings, Rejects, Good Evaluations, Scanned Profile Grading (based on decodability), Synchronized operation, Control of key printer or machine functions
- Applications:** AIAG-B1; AIAG-B3/B4/B5; LOGMARS; UCC/EAN/ITF

Verification Methods

- Verification Methods:** Traditional (except print contrast signal)
ANSI/CEN/ISO (decode and decodability only)
- Scanner Illumination:** Moving beam @ 670nm
- System Scan Rate:** 40 scans/second nominal
- System Analysis Time:** 50 ms nominal
- X Dimension:** 7.5 mil (0.19 mm) minimum

Environmental

- Operating Temperature:** 32 to 122° F (0 to 50° C)
- Storage Temperature:** -40 to 158° F (-40 to 70° C)
- Relative Humidity:** 5% to 95% Non-condensing

Symbologies

Code 39; Interleaved 2 of 5; EAN/UPC with addenda; Codabar; Code 128; Code 93

Model 10

Configuration

- Single, compact housing (controller/scanner)
- Powered by printer or applicator
- Mounting stand

Mechanical

- Keypad: 4-button (select, enter, F1, F2)
- Display: 2-line, 16 characters/line
- Size:
4.25" W x 7.5" H x 3.75" D
(10.7cm W x 19.0 cm H x 9.5 cm D)
- Weight: 2.2 lb. (0.997 kg)

Electrical

- Communication: RS-232
- Input Voltage: +5VDC; 300 mA max.
- LED Indicators: 6 (5 indicate output status, 1 indicates synchronization)
- Outputs: Open Collector: 250 mA sink max.; 24 VDC pull-up max.
- Inputs:
Switch Input:
 - Internal 10K pull-up to 5 VDC
 - External pull-up to 24 VDC max.Electrically Isolated Input:
 - 2-wire (+, -)
 - Input resistance 47K ohms
- Activation voltage +15 VDC to 100 VDC, 120Hz full rectified 100 VDC RMS acceptable

Safety/Regulatory

- FCC Class A, CE Certified



Interfaces

- QCOLVC10U — Unterminated Interface Cable Model 10
- QCOLVC004 — Sato 8400
- QCOLVC004A — Sato 8400 with rewinder
- QCOLVC005A — Zebra 140 (Cutter/Sync.)
- QCOLVC005B — Zebra 140 (Sync/Label Gap)Z
- QCOLVC007 — Prodigy
- QCOLVC009 — Zebra 105S/105SE/160S
- QCOLVCRS232 — Communication Cable—RS-232
- Kits
QCOLV1009 — Zebra Xi 140, 170 interface
QCOLV1010 — Zebra Xi11 90, 140, 170 i/f
QCOLV1011 — Zebra Xi11 220 interface
- Accessories
QCOLVPS — Power supply (external)
QCOLVUG — Operators manual
QCOLVSTD — Model 10 metal stand

Model 20

Configuration

- Separate controller and scanner
- Powered by internal power supply

Mechanical

- Keypad: 4-button (select, enter, F1, F2)
- Display: 2-line, 6 characters/line
- Size of Scanner:
3" W x 2.2" H x 6.1" D
(7.6cm W x 5.6 cm H x 5.5 cm D)
- Size of Control Box:
9.125" W x 9.125" H x 3.125" D
(23.2cm W x 23.2 cm H x 7.9 cm D)
- Weight: 4 lb. (1.8 kg)

Electrical

- Communication: RS-232
- Input Voltage: 115 VDC ± 10%; 60Hz
- Output Voltage: 24 VDC + 10%; 125mA max.
- LED Indicators: 6 (5 indicate output status, 1 indicates synchronization)
- Outputs:
Open Collector: 250 mA sink max.; 24 VDC pull-up max.
- Inputs:
Switch Input:
 - Internal 10K pull-up to 5 VDC
 - External pull-up to 24 VDC max.Electrically Isolated Input:
 - 2-wire (+, -)
 - Input resistance 47K ohms
- Activation voltage +15 VDC to 100 VDC, 120Hz full rectified 100 VDC RMS acceptable

Safety/Regulatory

- FCC Class A

Interfaces

- QCOLVC20U — Unterminated Interface Cable
- QCOLVCRS232 — Communication Cable — RS-232

Accessories

- QCOLV/UG — Operators manual

Worldwide Offices

Offices Serving North America

Skaneateles Falls, NY
Tel: (315) 685-8945
Fax: (315) 685-3172

Charlotte, NC
Tel: (704) 537-1444
Fax: (704) 532-4191

Offices Serving Europe, Middle East, and Africa

Europe
Tel: Int +31 (0) 40 24 24 486
Fax: Int +31 (0) 40 24 25 672

United Kingdom
Tel: Int +44 (0) 1 925 240055
Fax: Int +44 (0) 1 925 631280

France
Tel: Int +33 (0) 1 461 04111
Fax: Int +33 (0) 1 461 04120

Germany

Tel: Int +49 (0) 7 477 151377
Fax: Int +49 (0) 7 477 151378

Offices Serving Asia and the Pacific Rim

Hong Kong
Tel: Int +852 2511 3050/2511 3132
Fax: Int +852 2511 3557

Japan

Tel: Int +813 52127392
Fax: Int +813 32617372

Offices Serving Latin America

Naples, Florida
Tel: (941) 263-7600
Fax: (941) 263-9689

Web Site Address www.handheld.com

Welch Allyn Data Collection, Inc. and Hand Held Products, Inc. ("Hand Held Products") © 1999-2000, Hand Held Products. All rights reserved. Printed in the U.S.A.
Due to Hand Held Products' continuing product improvement programs, specifications and features herein are subject to change without notice.